

Sandlock: The Lightest AI Sandbox

Cong Wang

Founder and CEO, Multikernel Technologies, Inc.

The Industry Got the Threat Model Wrong

- Containers and microVMs were built for **adversaries** trying to escape
- AI agents are **not adversaries** , they follow your prompts
- The real threats: **prompt injection** and **agent mistakes**
- An agent runs `rm -rf /` not because it is malicious, but because it misinterpreted the prompt

"You do not need a hypervisor to stop `rm -rf /`. You need a filesystem allowlist."

Isolation Is Not Security

- A microVM agent can still read your **SSH keys** -- because you mounted them
- A container agent can reach **169.254.169.254** and steal IAM credentials
- All tools share the **same permissions** inside one big sandbox

"Isolation answers 'can it escape?' Security answers 'what can it access inside?'"

- The defense is **policy, not isolation**: deny by default, allowlist by path and host
- Per-tool-call sandboxing, not one box for everything

Rootless Sandboxing

Inside the sandbox: agents read files, write files, call APIs, none require root

Outside the sandbox: privileged infrastructure expands the blast radius

- Docker daemon runs as root; Firecracker needs `/dev/kvm`
- Privileged components become the target when isolation fails

The right approach:


- Unprivileged kernel interfaces: Landlock, seccomp-bpf, seccomp user notif
- No daemon, no root, no cgroups

What is Sandlock?

Lightweight process sandbox for Linux -- policy, not isolation

- **5ms startup**: fork() + apply policy + exec()
- **97% native performance**: near-zero steady-state overhead
- **No root, no cgroup, no VMs**: runs as a normal unprivileged user
- **Resource controls**: CPU & memory limits, process caps, disk quota
- **Per-tool-call sandboxing**: each tool gets its own policy
- **Built for AI**: HTTP ACL, COW filesystem, deterministic execution

Architecture



- **sandbox-core**: Rust library with async supervisor (tokio)
- **sandbox-cli**: Full-featured command-line interface

- **sandlock-ffi**: C ABI for Python and other language bindings



Three Layers of Enforcement

Layer 1: Landlock (kernel)
Filesystem read/write/exec per path
TCP port bind/connect restrictions
IPC scoping and signal isolation

Layer 2: seccomp-bpf (kernel)
Pre-compiled BPF bytecode (~1KB)
Blocklist (default) or allowlist mode
Near-zero overhead in kernel space

Layer 3: seccomp user notification (async)
Intercepts syscalls without killing proc
Resource limits, network ACL, COW, /proc
Tokio-based event loop in parent process

How It Works: Confinement Flow

After `fork()`, before `exec()`:

1. `PR_SET_NO_NEW_PRIVS` -- prevent privilege escalation
2. **Landlock** rules applied (filesystem + network + IPC)
3. **seccomp-bpf** filter installed
4. Notification FD sent to parent → parent starts **async supervisor**
5. Optional: vDSO patched for time/random virtualization

Total setup: ~5ms: no namespace, no cgroup, no mount

The Async Supervisor

The parent runs a **tokio event loop** intercepting syscalls:

Category	Syscalls	Action
Process	fork, clone, execve	Enforce process limit, policy callback
Memory	mmap, brk, mremap	Track anonymous memory usage
Network	connect, bind, sendto	IP allowlist, on-behalf execution
Filesystem	openat, unlinkat, mkdirat	COW interception, /proc virtualization
Determinism	getrandom, clock_nanosleep	Seeded PRNG, frozen time

Network Isolation

Domain-level allowlist:

- Resolve domains at sandbox creation → build IP allowlist
- `connect()` intercepted, checked, executed on behalf of child

HTTP-level ACL (method + host + path):

- Built-in MITM proxy for HTTPS inspection
- Fine-grained rules: `POST api.openai.com/v1/chat/completions`

Port virtualization:

- Multiple sandboxes can `bind()` the same port (e.g., 6379)
- Supervisor remaps to ephemeral ports transparently

Copy-on-Write Filesystem

Seccomp-based COW (no root, no mount namespace):

- Intercepts `openat`, `unlinkat`, `mkdirat`, `renameat2`
- Writes go to an **upper** directory; reads resolve upper-then-lower
- On exit: **commit** changes to workdir or **discard** (dry-run)

```
# Dry-run: preview what a build would change
sandlock run --dry-run --workdir . -w . \
  -r /usr -r /lib -r /bin -r /etc -- make build
```

/proc Virtualization

The sandbox sees an **isolated view** of the system:

- `/proc/cpuinfo` -- shows only allocated CPUs
- `/proc/meminfo` -- reports sandbox memory limit as total
- `/proc/loadavg` -- computed from sandbox's own processes
- `/proc/uptime` -- relative to sandbox start time
- `/proc/[pid]/*` -- only sandbox's own PIDs visible

"The confined process sees a consistent, isolated view -- as if it has the machine to itself."

Deterministic Execution

Frozen time:

- vDSO patched: `clock_gettime` returns fixed timestamp
- Timer syscalls adjusted by supervisor

Seeded randomness:

- `getrandom()` replaced with **ChaCha8 PRNG**
- `/dev/urandom` replaced with seeded memfd

```
sandbox run --time-start "2000-01-01T00:00:00Z" \  
--random-seed 42 -- ./build.sh
```

Same seed = same output, every time

COW `fork()`

- Initialize expensive state once (e.g., load ML model)
- `fork()` clones the process with shared COW memory
- Each child processes a shard independently
- **~530μs per fork, ~1,900 forks/sec**
- No full process restart, no VM overhead
- Ideal for low-latency parallel workloads

Pipelines for XOA Mode

Compose sandboxed stages with tight policies

```
[Planner: no data] --pipe--> [Executor: data, no network]
```

- Each stage has its own sandbox policy
- Data flows through kernel pipes only -- prevents exfiltration
- Planner can be networked while executor remains isolated
- Enables XOA mode: separate reasoning, action, and observation stages

Dynamic Policy Callbacks

```
def on_event(event, ctx):  
    if event.syscall == "execve" \  
        and event.argv_contains("curl"):  
        return True # deny  
  
    if event.category == "file" \  
        and "/secrets" in (event.path or ""):  
        return errno.EACCES  
  
    return 0 # allow  
  
result = Sandbox(policy, policy_fn=on_event).run(  
    ["python3", "untrusted.py"]  
)
```

- Per-syscall decisions with rich metadata
- Switch between setup and restricted phases at runtime

Per-Tool-Call Sandboxing

The problem: one sandbox for all tools = union of all permissions

Sandlock's approach: each tool invocation gets its own sandbox

```
Agent invokes "web_fetch" → fork + Sandbox(net only, no fs write)
Agent invokes "file_write" → fork + Sandbox(fs write, no net)
Agent invokes "run_tests" → fork + Sandbox(read-only src, no net)
```

- Fork + Landlock confinement in **< 1ms** per tool call
- A compromise of one tool cannot access another tool's permissions
- Least privilege at the **right granularity**: per-tool, not per-agent

Performance: Startup

Metric	Bare Metal	Sandlock	Docker
<code>/bin/echo</code> startup	2 ms	7 ms	307 ms
Overhead	--	+5 ms	+305 ms

- **44x faster** than Docker
- No image pull, no layer unpack, no namespace creation
- First run as fast as subsequent runs

Performance: Redis Benchmark

Metric	Bare Metal	Sandlock	Docker
Redis SET	82K rps	80K rps	52K rps
Redis GET	79K rps	77K rps	53K rps
p99 latency	0.5 ms	0.6 ms	1.5 ms

- **97% of native throughput**
- **2.5x lower tail latency** than Docker
- seccomp filters run in kernel -- near-zero per-syscall cost



CLI Usage

```
# Basic sandbox
sandlock run -r /usr -r /lib -w /tmp -- ls /tmp

# Resource limits (memory + processes) + timeout
sandlock run -m 512M -P 20 -t 30 -- ./compute.sh

# Network: allow only OpenAI API
sandlock run --net-allow-host api.openai.com \
  -r /usr -r /lib -r /etc -- python3 agent.py

# HTTP ACL: method + host + path
sandlock run \
  --http-allow "POST api.openai.com/v1/chat/completions" \
  --http-deny "* */admin/*" \
  -r /usr -r /lib -r /etc -- python3 agent.py
```



Python SDK

```
from sandlock import Sandbox, Policy

policy = Policy(
    fs_readable=["/usr", "/lib", "/etc"],
    fs_writable=["/tmp"],
    max_memory="256M",
    max_processes=10,
    http_allow=["POST api.openai.com/v1/chat/completions"],
)
result = Sandbox(policy).run(["python3", "agent.py"], timeout=30)
```

```
# Two-stage pipeline: planner (no data) -> executor (no network)
result = (
    Sandbox(planner_policy).cmd(["python3", "plan.py"])
    | Sandbox(executor_policy).cmd(["python3", "execute.py"])
).run()
```

Requirements & Availability

Kernel: Linux 6.12+ for full features (Landlock ABI v6)

Privileges: No root, no cgroups, no systemd, no kernel modules

Interfaces:

- **CLI:** `sandbox run ...`
- **Python:** `pip install sandbox`
- **Rust:** `sandbox-core` crate
- **C FFI:** `libsandbox_ffi.so`

Open source: github.com/multikernel/sandbox (Apache 2.0)

Key Takeaways

- The threat model is **policy, not isolation**
- Per-tool-call sandboxing: least privilege at the **right granularity**
- **44x faster startup** than Docker, **97% native throughput**
- **No root, no container, no VMs**
- HTTP ACL, COW filesystem, deterministic execution

"The lightest sandbox that doesn't compromise on security."

Questions and Feedback

Contact: cwang@multikernel.io

Open Source: github.com/multikernel/sandlock