

Why Unprivileged Containers Are Less Secure

Cong Wang

Founder and CEO, Multikernel Technologies, Inc.

The Most Misleading Names in Linux Security

"Rootless" and "unprivileged" containers tell you two true things:

- Rootless: the container runtime does not need root
- Unprivileged: root inside the container is not root on the host

What most people hear is a third thing:

- **A container with fewer privileges, therefore a safer one**

That third reading is backwards. A user namespace grants privileges.

Two Questions About a Sandbox

1. Identity (how bad a non-kernel breakout is): who is the process on the host?

- Root container: UID 0 on the host
- User namespace: an unprivileged UID, often your own
- Only matters for user-space escapes: a kernel exploit runs as the kernel

2. Reach (how likely a kernel breakout is): how much kernel code can it execute with arguments it controls?

- Most real escapes are kernel bugs, and a kernel bug only triggers from code you can reach

Ranked by reach: Sandlock < unprivileged user < user namespace < root

PART 1

A User Namespace Is a Bag of Capabilities

What `bwrap --unshare-user` actually hands you

What the Bag Holds

Capability	What it unlocks inside a user namespace
<code>CAP_SYS_ADMIN</code>	Mount tmpfs, proc, sysfs, overlayfs, FUSE; create mount, network, PID, IPC, UTS, cgroup, time namespaces
<code>CAP_NET_ADMIN</code>	Interfaces, routes, netfilter and nf_tables, tc qdiscs and filters, virtual devices
<code>CAP_NET_RAW</code>	Raw sockets, <code>AF_PACKET</code>
<code>CAP_SETUID</code> , <code>CAP_SETGID</code>	Write ID maps for nested namespaces, switch among mapped IDs
<code>CAP_SYS_CHROOT</code>	<code>chroot</code>
<code>CAP_CHOWN</code> , <code>CAP_DAC_OVERRIDE</code> , <code>CAP_FOWNER</code>	Bypass file permissions, on files owned by mapped IDs
<code>CAP_SYS_PTRACE</code> , <code>CAP_KILL</code>	Trace and signal processes in the namespace
<code>CAP_SYS_MODULE</code> , <code>CAP_SYS_RAWIO</code> , <code>CAP_BPF</code> , ...	Nothing: still checked against the host

Every Capability, One Syscall

```
$ B="bwrap --ro-bind / / --dev /dev --proc /proc --unshare-user --unshare-net"
$ $B grep CapEff /proc/self/status
CapEff: 0000000000000000      # bwrap drops them by default
$ $B --uid 0 --cap-add ALL grep CapEff /proc/self/status
CapEff: 000001ffffffffffff    # all 41 capabilities
$ $B python3 -c 'import os; os.unshare(os.CLONE_NEWUSER | os.CLONE_NEWNET); \
    print(open("/proc/self/status").read())' | grep CapEff
CapEff: 000001ffffffffffff    # dropped, then taken back with one syscall
```

- Inside the sandbox, `unshare(CLONE_NEWUSER|CLONE_NEWNET|CLONE_NEWNS)` still works: the user namespace comes first, its fresh capabilities create the rest
- Any user can configure interfaces, routes, netfilter, tc, and mount tmpfs, proc, sysfs, overlays, FUSE
- Scoped to that namespace, but **the kernel decides what that covers**
- `--disable-usersns` closes the nested path, but it is opt-in

capable() vs ns_capable()

```
/* fs/super.c */
bool mount_capable(struct fs_context *fc)
{
    if (!(fc->fs_type->fs_flags & FS_USERNS_MOUNT))
        return capable(CAP_SYS_ADMIN);
    else
        return ns_capable(fc->user_ns, CAP_SYS_ADMIN);
}
```

- `capable()` asks about the init user namespace: a normal user fails
- `ns_capable()` asks about **your** namespace: you own it, you pass
- Linux 7.0: **269** `ns_capable()`-family call sites, **129** in `net/`

PART 2

The CVE Record

Every bug behind a check a normal user fails, and a user namespace passes

Behind a Capability Check

CVE	Where	Capability	Outcome
CVE-2017-7308	AF_PACKET ring setup	CAP_NET_RAW	Heap overflow, local root
CVE-2018-18955	User namespace ID mapping	CAP_SYS_ADMIN + CAP_SETUID	Read host /etc/shadow
CVE-2020-14386	AF_PACKET receive path	CAP_NET_RAW	Heap overflow, local root
CVE-2021-22555	netfilter x_tables	CAP_NET_ADMIN	Local root, exploited in the wild
CVE-2022-0185	Filesystem context parsing	CAP_SYS_ADMIN	Kubernetes container escape
CVE-2022-0492	cgroup v1 release_agent	CAP_SYS_ADMIN	Code runs as host root
CVE-2023-0386	overlayfs copy-up	CAP_SYS_ADMIN	Host setuid binary, exploited in the wild
CVE-2023-32233	nf_tables	CAP_NET_ADMIN	Use-after-free, local root
CVE-2024-1086	nf_tables	CAP_NET_ADMIN	Local root, used by ransomware
CVE-2026-53075	PPP	CAP_NET_ADMIN	Administer a netns inherited from the host

Netfilter

CVE-2021-22555: heap OOB write in iptables compat code, there since 2.6.19

- Broke out of a pod in Google's kCTF Kubernetes cluster; CISA: exploited in the wild

CVE-2024-1086: nf_tables use-after-free. The public exploit's README requires:

- `CONFIG_USER_NS=y`, unprivileged user namespaces enabled, nf_tables enabled
- All three are **the default on Debian and Ubuntu**
- October 2025: CISA confirmed ransomware groups were using it

Filesystems and User Namespaces Themselves

CVE-2022-0185: integer underflow in `legacy_parse_param`, reached through `fsconfig`

- Needs `CAP_SYS_ADMIN`; the exploit got it with `unshare(CLONE_NEWNS|CLONE_NEWUSER)`

CVE-2023-0386: mount overlayfs in a user namespace, copy up a setuid file where the host honors it

- Added to CISA's exploited list in June 2025

CVE-2018-18955 (Jann Horn): nested ID maps with more than five ranges

- Create outer namespace, write a crafted map for the inner one, read `/etc/shadow`

Distros Already Know

- **Debian:** carried `kernel.unprivileged_usersns_clone` for years to turn it off
- **Hardened deployments:** `user.max_user_namespaces = 0`
- **Ubuntu 24.04:** apps may create a user namespace, but get no capabilities in it unless an AppArmor profile allows it
- **Qualys, March 2025:** three bypasses of Ubuntu's restriction, yielding a user namespace with full capabilities, described as a way to reach kernel bugs the restriction was meant to hide

Even the mitigation is attack surface.

PART 3

Going Below Unprivileged

Do not change who the process is, change what it can ask the kernel

Sandlock: Close the Way In

Sandlock: open source process sandbox for Linux 6.12+, built on Landlock, seccomp-bpf and seccomp user notification. No root, no namespaces, no cgroups.

Cannot create a user namespace

- seccomp denies `unshare`, `setns`, namespace flags on `clone`; no `clone3`
- Every bug in the table stays closed, even where user namespaces are on

Removes syscalls a normal user is allowed to make

- `bpf`, `perf_event_open`, `userfaultfd`, `keyctl`, `ptrace`, `io_uring_*`, raw sockets, ...
- Google, 2023: **60%** of kCTF exploit submissions targeted `io_uring`

Answer Syscalls in User Space

seccomp user notification routes selected syscalls to a supervisor process:

```
sandboxed: socket(AF_NETLINK, ..., NETLINK_ROUTE)
           | seccomp RET_USER_NOTIF
           v
supervisor: socketpair(AF_UNIX) -> inject one end (NOTIF_ADDFD)
           synthesize RTM_NEWLINK / RTM_NEWADDR for loopback only

kernel netlink / rtnetlink parser: never sees the request
```

- Other netlink protocols: rejected
- `/proc/cpuinfo`, `meminfo`, `mounts`, `/proc/net/*`: sealed memfd with synthesized content
- Sensitive `/proc` and `/sys` paths: denied

A Supervisor Bug Is Not a Kernel Bug

The supervisor parses untrusted input too. This **moves** attack surface.

Bug in	Attacker gets
Kernel netlink parser	the kernel
Sandlock supervisor	the user who started it: a normal user

Landlock confines what is left

- Paths: read, write, execute per directory tree
- Network: TCP `bind` and `connect` by port
- Scoping: abstract Unix sockets and signals stay inside the sandbox

Nested Sandlock

```
$ S=$(command -v sandlock)
$ sandlock run --no-supervisor -r /proc -r /usr -r /lib -r /lib64 -r /bin -r /etc -r $$ -w /tmp -- \
  $$ run -r /usr -w /tmp -- echo hello
hello
```

outer sandlock	Landlock + deny-only seccomp (incl. unshare, setns)
inner supervisor	parses untrusted input: netlink, /proc, network policy
AI agent	inner Landlock + seccomp, stacked on the outer

- **Outer, `--no-supervisor`:** kernel-only enforcement, no parser to exploit
- **Inner, supervised:** the full policy, virtualized netlink and `/proc`
- **Escape the inner, land in the outer:** still no user namespace, only the outer's paths
- Supervisor-free outer is required anyway: one seccomp listener per task

What User Namespaces Get Right

A tradeoff, not a verdict. User namespaces win on identity.

- **A different view:** private PID tree, mount table, network stack. Sandlock enforces policy on the existing view and virtualizes the leaky parts
- **Software that expects root:** a package manager in an image

Sandlock's UID/GID mapping is **opt-in**, and then it does use a user namespace:

- seccomp still applies inside: no mount, no other namespaces, no `CAP_NET_ADMIN`
- Documented as the exception it is

The Ranking

	Who you are after a breakout	Kernel reach
Root	root	everything
User namespace	an unprivileged UID	a normal user, plus every <code>ns_capable()</code> path
Unprivileged user	an unprivileged UID	the ordinary syscall interface
Sandlock	an unprivileged UID	a subset of the ordinary syscall interface

- A user namespace improves column 1 over root, and worsens column 2 over a normal user
- Sandlock keeps column 1 of a normal user and shrinks column 2 below it

Sandlock < unprivileged user < user namespace < root

Key Takeaways

- "Unprivileged" is about identity, not kernel reach
- User namespaces widen the way out, for **every** process on the host
- Measure a sandbox by how much kernel it can reach
- Nest Sandlock: an escape lands in another sandbox
- Turn unprivileged user namespaces off. Sandlock does not need them

Questions?

Contact: cwang@multikernel.io

Website: sandlock.io

Open Source: github.com/multikernel/sandlock

